




- Premium Quality
- EPDM Material Belts
- Manufactured under ISO 9001 : 2008
 Certificated Quality Management Standard

NEW Launch





1 Cover Fabric

Wear and crack resistant, flexible bias-cut cotton fabric impregnated with oil and heat resistant rubber compound.

2 Tensile Cords

Pre-Stretched strong polyester cords with less stretch and high horsepower capacity.

3 Rib Rubber

Fiber Chips reinforced rubber compound is used to provide high friction coefficient excellent wear resistant and high flexibility.

GenteQ Numbers:

Type Range: "Z", "A", "AX" and "BX"... types of belts.

Length: The Last three digit represents belt length e.g 350=35", 455=45.5", 530=53".

"REL" for Wrapped and Raw edge Plains belt

"REC" for Raw edge cogged belt

REL6230	REL1230	REC6230	REC8300	3PK630	4PK630	5PK820	6PK 955	7PK 990
REL6250	REL1235	REC6240	REC8310	3PK730	4PK645	5PK830	6PK1030	7PK1075
REL6255	REL1250	REC6250	REC8320	3PK735	4PK685	5PK835	6PK1040	7PK1140
REL6260	REL1255	REC6255	REC8330	3PK750	4PK700	5PK840	6PK1045	7PK1270
REL6270	REL1260	REC6260	REC8340	3PK760	4PK705	5PK850	6PK1050	7PK1470
& more	& more	& more	& more	& more	& more	& more	& more	& more

Enquries: (65) 6383 7545